

# ESSENZ

CARPETS MADE TO LAST

DURABLE

SOLID

RESILIENT



# PEMBRIDGE HEATHERS




▲ SB: PBH.0860 | 400 & 500 cm



▲ SB: PBH.0870 | 400 & 500 cm



▲ SB: PBH.0840 | 400 & 500 cm




▲ SB: PBH.0821 | 400 & 500 cm



▲ SB: PBH.0880 | 400 & 500 cm



▲ SB: PBH.0810 | 400 & 500 cm



▲ SB: PBH.0830 | 400 & 500 cm



▲ SB: PBH.0873 | 400 & 500 cm



▲ SB: PBH.0260 | 400 & 500 cm



▲ SB: PBH.0421 | 400 & 500 cm



▲ SB: PBH.0420 | 400 & 500 cm



▲ SB: PBH.0220 | 400 & 500 cm



▲ SB: PBH.0230 | 400 & 500 cm



▲ SB: PBH.0250 | 400 & 500 cm

# ESSENZ

CARPETS MADE TO LAST

DURABLE

SOLID

RESILIENT

# PEMBRIDGE HEATHERS

|  |  |   |   |
|--|--|---|---|
| Fabricagemethode<br>Technique de fabrication<br>Manufacturing process<br>Herstellungsart<br>Tecnica di fabbricazione<br><b>tufted,<br/>1/10" twist</b>                               | Poolsamenstelling<br>Nature du velours<br>Pile composition<br>Polmaterial<br>Composizione felpa<br><b>PP</b>   | Tuftdoek<br>Premier dossier<br>Primary backing<br>Trägermaterial<br>Tela di supporto<br><b>woven</b>  | Rugtype<br>Envers<br>Secondary backing<br>Rücken<br>Sottofondo<br><b>SB</b>   |
| Totale dikte<br>Hauteur totale<br>Total height<br>Gesamthöhe<br>Spessore totale<br><b>± 8,5 mm</b>   | Nuttige poolhoogte<br>Hauteur de velours utile<br>Effective pile height<br>Tatsächliche Florhöhe<br>Spessore felpa utile<br><b>± 6,0 mm</b>                                    | Breedte<br>Largeur<br>Width<br>Breite<br>Altezza<br><b>± 400 &amp; 500 cm</b>   | Aantal noppen/m <sup>2</sup><br>Nombre de points/m <sup>2</sup><br>Number of knots/sqm<br>Noppenzahl/m <sup>2</sup><br>Numero di punti/mq<br><b>± 157.600</b>                                     |
| Poolinzetgewicht/m <sup>2</sup><br>Poids mis en oeuvre/m <sup>2</sup><br>Pile weight/sqm<br>Poleinsatzgewicht/m <sup>2</sup><br>Peso felpa/mq<br><b>± 810 gr</b>                     | Totaal gewicht/m <sup>2</sup><br>Poids total/m <sup>2</sup><br>Total weight/sqm<br>Poleinsatzgewicht/m <sup>2</sup><br>Peso totale/mq<br><b>± 1.780 gr</b>                     | EN 13501-1<br>Brandgedrag<br>Comportement au feu<br>Fire behaviour<br>Brennverhalten<br>Reazione al fuoco<br><b>E<sub>fl</sub></b>  | EN 1307-2004<br>Classificatie<br>Classification<br>Classificazione<br>Klassifizierung<br><b>Class 22<br/>Domestic<br/>General</b>   |
| TOG rating<br><b>± 1,6</b>   | ISO 105 B02 2000<br>Lichtechtheid<br>Solidité à la lumière<br>Lightfastness<br>Lichtechtheid<br>Solidità colori alla luce<br><b>≥ 5</b>  | ISO 105 E01 2002<br>Waterrechtheid verkleuring<br>Solidité à l'eau changement couleur<br>Waterfastness change in colour<br>Wasserechtheit Änderung der Farbe<br>Solidità colori all'acqua cambio colore<br><b>≥ 3-4</b> | ISO 105 E01 2002<br>Waterrechtheid uitbloeding<br>Solidité à l'eau dégorgement<br>Waterfastness staining<br>Wasserechtheit anbluten<br>Solidità colori all'acqua sfumatura colore<br><b>≥ 2-3</b> |
| ISO 105 X12 2001<br>Wrijftechtheid droog<br>Solidité au frottement sec<br>Rubbingfastness dry<br>Reibungechtheit trocken<br>Solidità colori allo sfregamento a secco<br><b>≥ 3-4</b> | ISO 105 X12 2001<br>Wrijftechtheid nat<br>Solidité au frottement humide<br>Rubbingfastness wet<br>Reibungechtheit nass<br>Solidità colori allo sfregamento umido<br><b>≥ 3</b> |   |   |

(±) These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to improve technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. The natural characteristics of woollen products result in shade variations & slight blemishes. They cannot be avoided without destroying the very nature of the product itself. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet. For other languages see: [www.lano.com](http://www.lano.com)

