

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING
SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

DATE: 1/06/2022
REPLACES: 16/12/2021

SOFT PERFECTION SB
SPE

± 400-500
COLLECTION
1/10" CUT PILE

SOLUTION DYED

ECCELENA 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 2.640
± 3.590

± 15,0
± 17,0
± 185.180
± 39,40
± 47,00

±
±

± 25
PILE IN

✓
✓

NO SHOCK
✓

Cl. 22
Domestic General/Medium



LC5



Efl



Heavy non-domestic

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK




BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131


QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m²K/W	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

SOFT PERFECTION SB

± 25	
± 0,175	
± 1,75	
≤	
≥ 5	
≥ 3-4	
≥ 3	
≥ 3-4	
≥ 2-3	

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	<u>SPE</u>	<u>SB 500</u>
0242	CREAM 2	0242
0272	ALMOND 2	0272
0432	BAMBOO MAT 2	0432
0462	HEMP 2	0462
0832	ASH 2	0832
0842	MOONSHINE 2	0842
0844	MOONSHINE 4	0844
0862	GRANITE 2	0862
0872	SILVER 2	0872
0882	PEARL 2	0882

<u>SB 400</u>	<u>SPE</u>	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(10)

(10)