

QUALITY	
ORDER CODE	
WIDTH	(±) cm
TYPE	
GAUGE AND TYPE	
TEXTURING	
DYEING/PRINT METHOD	
PILE COMPOSITION	
FIBRE BRAND	
MOTHPROOF	
PRIMARY BACKING	
SECONDARY BACKING	
PILE WEIGHT	(±) gr/m ²
TOTAL WEIGHT	(±) gr/m ²
EFFECTIVE PILE HEIGHT	(±) mm
TOTAL HEIGHT	(±) mm
NUMBER OF KNOTS	(±) m ²
STITCHES OVER WIDTH	(±) / 10 cm
STITCHES OVER LENGTH	(±) / 10 cm
REPEAT TUFTING DESIGN L/W	(±) mm
REPEAT PRINTING DESIGN L/W	(±) mm
ROLL LENGTH	(±) m
PILE IN/OUT	

LANO CLASSIFICATION

BEDROOM	
LIVING ROOM	
OFFICE	
CASTOR ROLLCHAIRS DOMESTIC USE	
CASTOR ROLLCHAIRS PROFESSIONAL USE	
STAIRS DOMESTIC USE	
STAIRS PROFESSIONAL USE	
ELECTROSTATIC BEHAVIOUR	
UNDERFLOOR HEATING	
BATH ROOM	
NON-FRAY	
PERSONAL COMPUTER	
PRODIS-NUMBER	
GUT-NUMBER	
DIBT	
UPEC n°	
CLASSIFICATION	
HQE	
EN 1307	

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

DATE: 2/06/2020
REPLACES: 5/05/2020

EN 13501-1

BS 4790

JAIPUR SMB
JAI

± 400
COLLECTION
1/10 CUT PILE
SOLUTION DYED
PES
WOVEN
SMART BACK
± 770
± 1 755
± 8,5
± 12,0
± 236 400
± 39,40
± 60,00
±
±
± 30
PILE OUT

✓

✓

✓

Cl. 22
Domestic General/Medium



LC3

QUALITY

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25

THERMAL RETENTION

(±) m²K/W

ISO 8302

± 0,15

TOG rating

(±)

± 1,5

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE FROM

AVAILABLE FROM

SMB 400

JAI

0780

STEEL

0820

SLATE

0830

ASH

0840

MOONSHINE

0850

MOONBEAM

SMB 400

JAI



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(5)