

Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Aiguilleté plat en dalle / Flat needlefelt in tile
Type d'enduction / Type of bonding		Enduction d'envers / Back coated
Composition des fibres de surface / Fiber composition of surface		45% Polyamide dorig®, 30% Polypropylène, 25% Polyester
Masse totale de surface / Total weight of surface	ISO 8543	540 g/m ²
Masse totale / Total Weight	ISO 8543	4360 g/m ²
Epaisseur totale / Total Thickness	ISO 1765	6,6 mm
Envers / Backing		Matières recyclées renforcées par un voile de verre / Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		16 = 4 m ²
Sens de pose / Installation		

Technical performances



Classification EN 1307 - 33 / Commercial Heavy

Luxury Class - LC1



Classement UPEC NF 262 - U₃P₃E₁C₀ (certificat n° 349TA-005.1)

Feu / Fire rating EN 13501-1 : BflS1



		RHO - LRV	
		10 colors	%
Heated Floor ISO 10456 0,09 m ² K/W	Impact noise reduction EN ISO 10143-3 ΔL _(w) 21 dB	001	10,3%
		002	15,2%
		004	16,0%
Castor Chair EN 985 Passed R ≥ 2,4	Sound absorption ISO 11654 α _w = 0,15 (H)	006	6,0%
		008	3,5%
Dimensional Stability EN 986 ≤ 0,10%	Colour Fastness EN 105 - B02 ≥ 6/8	011	5,7%
		012	4,4%
 N° 0679-CPR-0200 08 EN 14041 : 2004	Electrostatic prop. ISO 6356 ≤ 2,0kV ISO 10965 RT ≤ 10 ⁹ Ω Propriété dissipatrice / Dissipative Property	013	5,0%
		014	5,0%
		015	7,1%

Environmental issues

LEED

