

WOVON

The Polyflor Wovon interwoven vinyl flooring a collection of diverse weave designs offering a varied yet unmistakable textile feeling. With the advantages of its heavy commercial vinyl construction the Wovon collection is a hard wearing, low maintenance option for commercial and residential locations. Such areas include Office, Retail and Hotels.



	Gauge	ISO 1765	3.1mm
	Tile Size	EN 944	16 @ 500 x 500mm = 4m ²
	Total Weight	ISO 8543	3750g/m ²
	General Performance	EN 1307	
	Acoustic Impact Sound Reduction	EN ISO 10140-3	≥11dB
	Reaction to Fire	EN 13501-1	Bfl-S1
	Abrasion Resistance	EN 1963 Test A	Class 23/33
	Slip Resistance	DIN 51130 EN 13893 AS 4586	R10 DS R10
	Residual Indentation	EN 433	<0.1mm
	Furniture Leg Test	EN 424	Pass
	Castor Chair (continuous use)	EN 985C	Pass
	Dimensional Stability	ISO 2551	<0.1%
	Curling After Exposure to Heat	EN 434	≤2mm
	Thermal Conductivity	EN 12667	0.153 W/m ² .K
	Thermal Resistance	EN 12667	0.185m ² .K/W
	Underfloor Heating Suitability	-	Suitable max 27°C
	Electrical Behaviour (body voltage)	EN 1815	≤2kV
	Light Fastness	EN ISO 105-B02	≥6
	VOC Emissions	AgBB VOC test	Pass low emissions



For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com.
The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.
Decoration and shade may vary slightly from the samples shown.

