

QUALITY
ORDER CODE

DATE: 13/04/2018
REPLACES: 21/12/2010

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

SATINE KT
SAT

± 400 & 500
COLLECTION
1/10" SAXONY

PIECE DYED

PA 6.6

WOVEN

TEXTILE BACKING C-BACK

± 1 470
± 2.630

± 7,0
± 9,5
± 165.480
± 39,40
± 42,00

±
±

± 30
PILE IN

✓
✓
✓
✓
✓
✓
✓
✓

BOF27C34

24395
Z-156.601-952 - PA 6.6 / 121

10/264
U2sP3E1C0

CL. 23 - CL. 32
Domestic Heavy - Commercial General



LC5



Cfl-s1



QUALITY

DIMENSIONAL STABILITY

EN 986

SATINE KT

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 24



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

± 0,03

(±)

250Hz

± 0,05

(±)

500Hz

± 0,13

(±)

1000Hz

± 0,47



(±)

2000Hz

± 0,47

(±)

4000Hz

± 0,67

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,25

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,079



TOG rating

(±)

± 0,79

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE R_{oT}

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE R_{dT}

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4-5

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4-5

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 4-5

WATERFASTNESS STAINING

ISO 105-E01

≥ 4-5

LABEL CE



ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - SHORT PIN MUSHROOM TAPE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

KT 400	SAT	KT 500
031	LILAC 1	031
052	CROCUS 2	052
081	PURPLE 1	081
091	AUBERGINE 1	091
101	RUBY 1	101
121	CORAL 1	121
141	OLD ROSE 1	141
152	SAHARA 2	152
200	CHOCOLATE	200
221	ACORN 1	221
230	FLAX	230
240	CREAM	240
250	MAGNOLIA	250
280	HAVANNA	280
321	COGNAC 1	321
371	GOLD 1	371
372	GOLD 2	372
411	LEATHER 1	411
430	BAMBOO MAT	430
482	BARLEY 2	482
572	MOSS 2	572
662	CELADON 2	662
731	AZURE 1	731
751	SKY 1	751
791	MIDNIGHT 1	791
800	EBONY	800
820	SLATE	820

KT 400	SAT	KT 500
841	MOONSHINE 1	841
850	MOONBEAM	850
880	PEARL	880

(30)

(30)



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE