

EXTRAVAGANCE

SOFT ORIGINS COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 5/16" cut pile Tufté 5/16" cut pile Getuftet 5/16" cut pile Getuft 5/16" cut pile	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	>=5
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PES	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	>=4-5
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Twin back	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 E _{FL} -s1
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 1.760 gr/m ²	WIDTH LARGEUR BREITE BREEDTE	ca. 400 cm
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.600 gr/m ²		
PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 16 mm		
TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 20 mm		
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 21.000/m ²		
PRODIS / GUT	2FDCC410		
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 21 - LC5		

balta



BALTA INDUSTRIES
Wakkensteenweg 2, B-8710 Sint-Baafs-Vijve
balta-carpets.com

EN 14041
CE
21
BALTA INDUSTRIES Wakkensteenweg 2 - BE 8710 Sint-Baafs-Vijve
DOP: 1010#BN0AEL
Textile Floor Covering EN1307

www.baltamediabank.com