

QUALITY
ORDER CODE

DATE: **23/04/2018**
REPLACES: 18/09/2013

WIDTH (±) cm

TYPE

GAUGE AND TYPE

TEXTURING

DYEING/PRINT METHOD

PILE COMPOSITION

FIBRE BRAND

WOOLMARK

MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²

TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm

TOTAL HEIGHT (±) mm

NUMBER OF KNOTS (±) m²

STITCHES OVER WIDTH (±) / 10 cm

STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm

REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m

PILE IN/OUT

LANO CLASSIFICATION

BEDROOM

LIVING ROOM

OFFICE

CASTOR ROLLCHAIRS DOMESTIC USE

CASTOR ROLLCHAIRS PROFESSIONAL USE

STAIRS DOMESTIC USE

STAIRS PROFESSIONAL USE

ELECTROSTATIC BEHAVIOUR

UNDERFLOOR HEATING

BATH ROOM

NON-FRAY

PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER

DIBT

UPEC n°

CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION

CLASSIFICATION BS7131

GODIVA KT
GOD

± 400 & 500
COLLECTION
1/10" CUT PILE

PIECE DYED

PA 6.6

WOVEN

TEXTILE BACKING C-BACK

± 900

± 2 020

± 6,5

± 8,5

± 283.680

± 39,40

± 72,00

±

±

± 25

PILE OUT

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

E3ABF25D

20894

Z-156.601-952 - PA 6.6 / 121

Cl. 23 / Cl. 32

Domestic Heavy / Commercial General



LC4



Cfl-s1



QUALITY				GODIVA KT	
DIMENSIONAL STABILITY			EN 986	≤	
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 27	
SOUND ABSORPTION	(±)	α _s	ISO 354 - 125 Hz	±	
	(±)		250Hz	± 0,03	
	(±)		500Hz	± 0,1	
	(±)		1000Hz	± 0,41	
	(±)		2000Hz	± 0,46	
	(±)		4000Hz	± 0,56	
SOUND ABSORPTION	(±)	α _w	EN ISO 11654	± 0,2	
THERMAL RETENTION	(±) m²/KW		ISO 8302	± 0,091	
TOG rating	(±)			± 0,91	
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤ 2000	
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤ 10 E10	
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤ 10 E11	
LIGHTFASTNESS			ISO 105-B02	≥ 6	
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 4-5	
RUBBINGFASTNESS WET			ISO 105 X12	≥ 4-5	
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 4	
WATERFASTNESS STAINING			ISO 105-E01	≥ 4	
LABEL CE					13 CE EN 14041 DOP 1038-111937 NB 2401  LANO NV - Venetijelaan 33 B-8530 HARELBEKE Floor carpets to use in buildings
RECOMMENDED INSTALLATION					ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - SHORT PIN MUSHROOM TAPE
MANUFACTURING TOLERANCE					

QUALITY				GODIVA KT	
DIMENSIONAL STABILITY			EN 986	≤	
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 27	
SOUND ABSORPTION	(±)	α _s	ISO 354 - 125 Hz	±	
	(±)		250Hz	± 0,03	
	(±)		500Hz	± 0,1	
	(±)		1000Hz	± 0,41	
	(±)		2000Hz	± 0,46	
	(±)		4000Hz	± 0,56	
SOUND ABSORPTION	(±)	α _w	EN ISO 11654	± 0,2	
THERMAL RETENTION	(±) m²/KW		ISO 8302	± 0,091	
TOG rating	(±)			± 0,91	
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤ 2000	
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤ 10 E10	
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤ 10 E11	
LIGHTFASTNESS			ISO 105-B02	≥ 6	
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 4-5	
RUBBINGFASTNESS WET			ISO 105 X12	≥ 4-5	
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 4	
WATERFASTNESS STAINING			ISO 105-E01	≥ 4	
LABEL CE					13 CE EN 14041 DOP 1038-111937 NB 2401  LANO NV - Venetijelaan 33 B-8530 HARELBEKE Floor carpets to use in buildings
RECOMMENDED INSTALLATION					ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - SHORT PIN MUSHROOM TAPE
MANUFACTURING TOLERANCE				</	

