

QUALITY  
ORDER CODE

DATE: 18/07/2019  
REPLACES: 13/02/2018

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**HARMONY SMB**  
**HRM**

± 400 & 500  
COLLECTION  
1/10" CUT PILE

PIECE DYED

PA

WOVEN

SMART BACK

± 1.265  
± 2.260

± 7,5  
± 9,5  
± 165.480  
± 39,40  
± 42,00

±  
±

± 25  
PILE IN

✓  
✓  
✓  
✓  
✓  
✓

ANTISTATIC  
✓

C67F61C0

Cl. 32  
Commercial General



LC4



Bfl-s1



QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m <sup>2</sup> /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

**HARMONY SMB**

± 25



± 0,15

± 1,5

≤ 2000




≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SMB 400</u>	<b>HRM</b>	<u>SMB 500</u>
090	AUBERGINE	090
110	CARMINE	110
120	CORAL	120
150	SAHARA	150
210	TOBACCO	210
250	MAGNOLIA	250
440	IVORY	440
450	SAND	450
720	BLUE CAPE	720
780	STEEL	780
790	MIDNIGHT	790
810	CHARCOAL	810
830	ASH	830
860	GRANITE	860
870	SILVER	870
880	PEARL	880

<u>SMB 400</u>	<b>HRM</b>	<u>SMB 500</u>
----------------	------------	----------------



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(16)

(16)