

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

DATE: 15/11/2018
REPLACES: 29/04/2016

HEATHERTWIST SUPREME SB
HRS

± 400 & 500
COLLECTION
1/8" TWIST

SOLUTION DYED

PP

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.360
± 2.390

± 8,5
± 10,5
± 132.300
± 31,50
± 42,00

±
±

± 30
PILE IN

LANO CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

✓
✓

NO SHOCK
✓

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

LC4



FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

Efl



LOW RADIUS



LANO CLASSIFICATION
CLASSIFICATION BS7131

HEAVY NON-DOMESTIC

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m ² /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

HEATHERTWIST SUPREME SB

± 25	
± 0,103	
± 1,03	
≤	
≥ 5	
≥ 3-4	
≥ 3	
≥ 3-4	
≥ 2-3	



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	HRS	<u>SB 500</u>
0201	CHOCOLATE 1	0201
0231	FLAX 1	0231
0241	CREAM 1	0241
0271	ALMOND 1	0271
0281	HAVANNA 1	0281
0401	COFFEE 1	0401
0441	IVORY 1	0441
0815	CHARCOAL 5	0815
0823	SLATE 3	0823
0843	MOONSHINE 3	0843
0853	MOONBEAM 3	0853
0861	GRANITE 1	0861
0863	GRANITE 3	0863
0871	SILVER 1	0871
0881	PEARL 1	0881

<u>SB 400</u>	HRS	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(15)

(15)