

QUALITY  
ORDER CODE

DATE: 12/02/2021  
REPLACES: 13/01/2021

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
MOTHPROOF

PRIMARY BACKING  
SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**TRAVIATA SMB**  
**TRV**

± 400 & 500  
COLLECTION  
5/64" CUT PILE

PIECE DYED

PA

WOVEN

SMART BACK

± 1.540  
± 2.510

± 5,5  
± 8,0  
± 252 000  
± 50,40  
± 50,00

±  
±

± 25  
PILE IN


✓  
✓  
✓  
✓  
✓  
✓


✓

D24F61BE

Cl. 23 / Cl. 32  
Domestic Heavy / Commercial General



LC5 

Bfl-s1 

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m²K/W	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

**TRAVIATA SMB**

± 25



± 0,08



± 0,8

≤


≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SMB 400</u>	<b>TRV</b>	<u>SMB 500</u>
0070	VIOLET	0070
0110	CARMINE	0110
0230	FLAX	0230
0250	MAGNOLIA	0250
0380	BRONZE	0380
0390	COPPER	0390
0410	LEATHER	0410
0420	CORNSTALK	0420
0430	BAMBOO MAT	0430
0440	IVORY	0440
0480	BARLEY	0480
0680	JUNIPER	0680
0780	STEEL	0780
0790	MIDNIGHT	0790
0810	CHARCOAL	0810
0820	SLATE	0820
0830	ASH	0830
0860	GRANITE	0860
0870	SILVER	0870

<u>SMB 400</u>	<b>TRV</b>	<u>SMB 500</u>
----------------	------------	----------------



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE