

QUALITY  
ORDER CODE

DATE: **29/10/2019**  
REPLACES: 2/09/2019

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**SWEET DREAMS SB**  
**SWD**

± 400-500  
COLLECTION  
1/8" CUT PILE

SOLUTION DYED

PP

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.390  
± 2.360

± 10,5  
± 13,0  
± 126.000  
± 31,50  
± 40,00

±  
±

± 25  
PILE IN

✓  
✓

✓

NO SHOCK  
✓

Cl. 22  
Domestic General/Medium



LC5



Efl



MEDIUM RADIUS

HEAVY DOMESTIC / GENERAL NON-DOMESTIC

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m²/KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

**SWEET DREAMS SB**

± 25



± 0,175



± 1,75

≤


≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	<b>SWD</b>	<u>SB 500</u>
0230	FLAX	0230
0240	CREAM	0240
0430	BAMBOO MAT	0430
0440	IVORY	0440
0450	SAND	0450
0820	SLATE	0820
0830	ASH	0830
0840	MOONSHINE	0840
0850	MOONBEAM	0850
0860	GRANITE	0860
0870	SILVER	0870
0880	PEARL	0880

<u>SB 400</u>	<b>SWD</b>	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(12)

(12)