

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

DATE: 23/10/2018
REPLACES: 7/12/2011

SQUARE SB
SQS

± 400
COLLECTION
1/10" CUT PILE

PIECE DYED

PA 6.6

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 900
± 2.060

± 4,5
± 7,5
± 204 880
± 39,40
± 52,00

±
±

± 32
PILE IN

✓
✓
✓
✓
✓
✓
✓
✓
✓
✓

ANTISTATIC

61E3BFCE

20758

12/292
U3sP3E1C0

✓

CL. 33
Commercial Heavy



LC3



Bfl-s1



LOW RADIUS

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

± 0,01

(±)

250Hz

± 0,03

(±)

500Hz

± 0,1

(±)

1000Hz

± 0,23

(±)

2000Hz

± 0,48

(±)

4000Hz

± 0,52



SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,2

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,067



TOG rating

(±)

± 0,67

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2000



SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤ 10E11

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤ 10E10

LIGHTFASTNESS

ISO 105-B02

≥ 6

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 4

WATERFASTNESS STAINING

ISO 105-E01

≥ 4

LABEL CE

11 **CE**
EN 14041
DOP 1038-111947
NB 0493



LANO NV - Venetiëlaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

| <u>SB 400</u> | SQS |
|---------------|-------------|
| 122 | CORAL 2 |
| 183 | RUM 3 |
| 252 | MAGNOLIA 2 |
| 262 | CAMEL 2 |
| 282 | HAVANNA 2 |
| 312 | RUST 2 |
| 403 | COFFEE 3 |
| 452 | SAND 2 |
| 462 | HEMP 2 |
| 682 | JUNIPER 2 |
| 701 | NAVY 1 |
| 772 | SAPPHIRE 2 |
| 811 | CHARCOAL 1 |
| 822 | SLATE 2 |
| 823 | SLATE 3 |
| 842 | MOONSHINE 2 |
| 862 | GRANITE 2 |

| <u>SB 400</u> | SQS |
|---------------|------------|
|---------------|------------|



