

QUALITY  
ORDER CODE

DATE: 10/10/2019  
REPLACES: 9/10/2019

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

#### LANO CLASSIFICATION

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

#### SCALA CLASSIC IB SCB

± 400  
COLLECTION  
1/10" CUT PILE

SOLUTION DYED

PP

WOVEN

IMPERVIOUS BACKING

± 1.160  
± 2.810

± 5,0  
± 8,0  
± 189.120  
± 39,40  
± 48,00

± 60,0/30,0  
±

± 30  
PILE IN

✓

✓

NO SHOCK

✓

✓

Cl. 22  
Domestic General/Medium



LC3



Efl



LOW RADIUS

Heavy contract / Extra-Heavy domestic  
HEAVY NON-DOMESTIC

QUALITY

DIMENSIONAL STABILITY

EN 986

≤



IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 30

SOUND ABSORPTION

(±)

$\alpha_s$

ISO 354 - 125 Hz

± 0,02

(±)

250Hz

± 0,04

(±)

500Hz

± 0,09

(±)

1000Hz

± 0,3

(±)

2000Hz

± 0,4

(±)

4000Hz

± 0,46



SOUND ABSORPTION

(±)

$\alpha_w$

EN ISO 11654

± 0,2

THERMAL RETENTION

(±) m<sup>2</sup>/KW

ISO 8302

± 0,076



TOG rating

(±)

± 0,76

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

LIGHTFASTNESS

ISO 105-B02

≥ 6

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4-5

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4-5

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 4-5

WATERFASTNESS STAINING

ISO 105-E01

≥ 4-5

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE  
FROM

AVAILABLE  
FROM

COLOURS



| <u>IB 400</u> | <b>SCB</b> |
|---------------|------------|
| 0100          | RUBY       |
| 0230          | FLAX       |
| 0270          | ALMOND     |
| 0420          | CORNSTALK  |
| 0480          | BARLEY     |
| 0770          | SAPPHIRE   |
| 0790          | MIDNIGHT   |
| 0810          | CHARCOAL   |
| 0820          | SLATE      |
| 0830          | ASH        |
| 0860          | GRANITE    |
| 0870          | SILVER     |

| <u>IB 400</u> | <b>SCB</b> |
|---------------|------------|
|---------------|------------|

WE RESERVE THE RIGHT TO  
ALTER TECHNICAL SPECIFICATIONS  
WITHOUT PRIOR NOTICE

(12)