

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

DATE: 30/03/2018
REPLACES: 26/01/2018

SCALA TWIST
SCI

± 400
COLLECTION
1/8" TWIST

SOLUTION DYED

PP

WOVEN

IMPERVIOUS FOAMBACK

± 1.200
± 2.720

± 8,0
± 11,0
± 129.150
± 31,50
± 41,00

±
±
±

LANO CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

✓
✓

NO SHOCK
✓
✓

Cl. 31
Commercial Moderate



LC4



Efl



LOW RADIUS

Heavy contract / Extra-heavy domestic

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

