

REX

LCT COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Needlefelt Aiguilleté Nadelvlies Naaldvilt	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PP	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 3-4
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Betumen back Min. 70% recycled content	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 B _{F,L} -1
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 650 gr/m ²	SIZE DIMENSION ABMESSUNG AFMETING	50 X 50 cm
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.850 gr/m ²	PACKAGING EMBALLAGE VERPACKUNG VERPAKKING	5 m ² /b 20 p/b
PILE THICKNESS EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 4,0 mm		
TOTAL THICKNESS EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 6,0 mm		
PRODIS / GUT	CCF0DB8E		
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 21 - LC2		

itc



EN 14041
CE
11
ITC Kanegemstraat 15 - BE 8700 Tielt
DOP: 1022#BJ0ABV
Textile Floor Covering EN 1307:2014
www.itc-carpets.com